

Electronic heat cost allocator with integrated data transmitter

## E-ITN 30.6 - WIRELESS M-BUS

### DESCRIPTION

E-ITN 30.6 is a modern electronic device intended for ratio based allocation of heat cost in buildings with central heating system. The allocator can be used for yearly and monthly billing periods. The heat cost allocator E-ITN 30.6 uses the 2 sensor measuring principle. One sensor measures the temperature of the radiator and the second sensor measures the temperature of the room. Using this principle, allocator ensures exact measurement of consumption value only when the radiator really emits heat.

### DATA READING

Due to integrated radio transmitter, presence of flat occupant is not required when data are read. No strangers enter the flat. Data reading can be made by billing company employee using mobile receiving unit. When everyday online access to the data is required, the data can be also read by central reading system permanently installed in the building. The radio transmitted data can provide you with the following information: serial number of the device, date of billing period beginning, date of reading, date of breaking the electronic seal, consumption value for the current year billing period, consumption value for the current monthly billing period, consumption value for the previous month billing period, average temperature for the previous month billing period.

### USER CONTROL

Every user can control current value during billing period and archive value for past billing period on LCD display. LCD is for better accessibility placed on the top side of the fashionably designed allocator.

### PROTECTION AGAINST CHEATING

The heat cost allocator E-ITN 30.6 is equipped with electronic seal. This seal is able to recognize unauthorized manipulation and record its exact date. Data about unauthorized manipulation is transmitted in radio signal. When thermally influenced, allocator is switched to single sensor mode. Allocator is switched back to standard two-sensor mode when thermal influence is finished. Consumption values and radiator temperatures for past 12 months can be read from the allocator memory via infra-red interface.

### CIPHERING

The heat cost allocator E-ITN30.6 has the option of ciphering using AES - 128 (the block size of the ciphered data is 128 bits, the size of the key is 128 bits). The key consists of two parts - the first defined by the manufacturer specifically for each partner, the second part can be specified by the partner in the setting protocol.

### APPLICATION

E-ITN 30.6 is intended to be installed in one-tube horizontal/vertical and two-tube heating systems with the lowest design heating medium temperature  $\geq 35^{\circ}\text{C}$  and highest mean design heating medium temperature  $\leq 105^{\circ}\text{C}$ .



**TECHNICAL DATA**

<b>Communication protocol</b>	W-MBUS according to ČSN EN 13757-4
<b>Measuring method</b>	Two sensor principle
<b>Conditions of measuring</b>	Sensor temperature of the radiator $\geq 23^{\circ}\text{C}$ temperature difference between the mean heating medium temperature and the reference air temperature $\leq 5\text{K}$ , (according to EN834:2013), different conditions for registration in the summer period
<b>Resulting rating factor</b>	Individual scale
<b>Calendar functions</b>	Consumption values for current, previous and penultimate year billing period; monthly consumption values; minimum, average and maximum temperatures on the radiator sensor; number of days when and increase of consumption value was registered
<b>Data displaying</b>	5-digits LC display + 2 special characters
<b>Data reading</b>	Visual, radio and infra-red interface
<b>Protection against cheating</b>	If the thermal influence is detected, allocator is switched to single-sensor mode Mechanical seal with marking of the operating company Elektronical seal records manipulation date when uninstalled
<b>Data backup</b>	Daily backup of measured values including actual time
<b>Function control</b>	Automatic, can be activated and controlled by user
<b>Dimension</b>	100x37x33 mm
<b>Power supply</b>	Lithium battery 3,0 V
<b>Material</b>	ABS + PC/AL - F22
<b>IP</b>	IP 42
<b>Conformity</b>	EN 834
<b>Operating frequency</b>	868,95 MHz
<b>Transmitting power</b>	<5 mW
<b>Transmission length</b>	~5 ms
<b>Transmission range</b>	Up to 250 m (without entering the building, with addition panel antenna) Note.: All metal parts of construction (armouring, lifts, switch rooms etc.) can negatively affect the range of radio signal
<b>Data ciphering</b>	Optional AES 128, (the block size of the ciphered data is 128 bits, the size of the key is 128 bits)

**CONTACTS****APATOR METRA s.r.o.**

Havlíčková 919/24

787 01 Šumperk

Czech Republic

Tel.: +420 583 718 261

E-mail: prodej@metra-su.cz

Web: www.metra-su.cz

Your distributor:

The manufacturer reserves the right to change design, technical specification and accessories without prior notice.

K2024/04a