

Electronic radio modules for residential water meters Apator Powogaz

APT-03A-3**DESCRIPTION**

The APT-03A-3 is designed for household water meter reading and wireless data transmission. Data is transmitted by Wireless M-Bus radio connectivity in accordance with the PN-EN 13757 standard and the Open Metering System Volume 3 specification. The open communication protocol provides compatibility with a wide range of device forming the remote data readout and transmission structure. The device is based on a microprocessor system, while the use of optical sensors enables, for example, data readout from water meters and detection of water flow direction, which provides complete consistency of radio-based readouts and water meter readings. The device is resistant to strong external magnetic fields, and the battery power enables continuous operation for up to 12 years. The device uses a data encryption method based on the AES-CBC algorithm with a 128 bit encryption key, which protects against unauthorised access to measurement data and guarantees the integrity of data sent to the system.

**APPLICATION**

The device is intended for installation on apartment water meters of the following types: JS 6,3 Master+, JS 10 Master+, JS 10-G1¼ Master+, JS 16 Master+, JS 6,3 Master C+, JS 10 Master C+, JS 10-G1¼ Master C+, JS 16 Master C+, vyrobených firmou Apator Powogaz S.A.

FEATURES

- Non-integrating and easy to install on water meters
- Quick and easy setting with mobile devices
- Operates in the 868 MHz unlicensed ISM band
- Data transmission encrypted using the AES-CBC encryption with 128 bit encryption keys, compliant with the PN-EN-13757-3 standard
- Real time clock with winter/summer time and leap year features
- Water meter type selection and configurable water meter-related properties
- Five operating modes enable adjustment of the data transmission interval to the user's individual requirements
- Detection, recording and signalling of irregularities on water consumption measurements and clip-on module operation using event signalling
- Option of storing and reading the volume from 1 to 16 months
- Water consumption readout using mobile terminals in a mobile data collection system or using a telemetry network in a fixed system
- Measurement data readouts from water meters are completely resistant to all interference caused by external magnetic fields
- Compatibility with devices in the automatic meter reading and measurement data transmission infrastructure that are compatible with the Open Metering System Volume 3 specification
- Optimum range achieved using an external antenna with counterweighting on the antenna track (for model 2.65.H.1.09)

DEVICE OPERATING MODE

- First hourly mode
- Second hourly mode
- Days of the week mode
- Days of the month mode
- Months mode

EVENT SIGNALLING

	Maximum flow
	Minimum flow
	Backflow
	No change in measurement
	Leakage
	Device disconnection
	Magnetic field detection
	Strong light detection
	Low battery
	Battery work time exceeded
	Battery usage threshold exceeded
	Tip error
	Instruction completed
	Processor reset
	Incorrect log value in processor
	Access error

CONFIGURATION OPTIONS

- Measurement device factory number
- ID number
- UID number
- Measuring device positioning
- Volume
- Reading memorisation day
- Metering threshold unchanged
- Minimum flow threshold
- Maximum flow threshold
- Reverse flow threshold
- Leak threshold
- Auto-reset of events

TECHNICAL DATA

Parameters	Model	
	2.65.1.1.03	2.65.H.1.09
Communication protocol	Wireless M-Bus	Wireless M-Bus
Transmission frequency	868 MHz	868 MHz
Consumption detection	Optical	Optical
Power supply	Lithium battery 3.6 V; 1/2 AA	Lithium battery 3.6 V; 1/2 AA
Ingress protection rating	IP 65	IP 65
Signal lead	Internal antenna	External antenna on 2 m long antenna track
Power output	10mW / 50Ω	10mW / 50Ω
Power output level stability	+1 dB ÷ -3 dB	+1 dB ÷ -3 dB
Sensitivity	-102 dB	-102 dB
Battery lifetime (depending on configuration)	Up to 12 years*	Up to 12 years*
Mounting	Directly on the water meter	Directly on the water meter
Dimensions	v=44,1 mm; s=65,5 mm	v=44,1 mm; s=65,5 mm
Weight	0,056 kg	0,065 kg
Operating temperature	0°C ÷ 55°C	0°C ÷ 55°C

*For devices operating at 25°C ambient temperature

CONTACTS

APATOR POWOGAZ CZECHIA s.r.o.

Havlíčková 919/24

787 01 Šumperk

Czech Republic

Tel.: +420 583 718 261

E-mail: prodej@metra-su.cz

Web: www.apator.cz

Your distributor:

The manufacturer reserves the right to change design, technical specifications and accessories without prior notice.

K2025/10a