

## **THERMOSTAT TH 160**

TH 169

60-120

2÷8

315


388


250 V, 15 A AC

2

DESCRIPTION	Thermostat consists of a stem (temperature sensor) and a switch head. Changes of sensor dialtation are transferred via lever to a switch. Thermostats are made either in disconnecting design (2 terminals) or in switching design (3 terminals). Screw terminal allow to connect wires with diameter up to 4 mm. Protective cable must be connected to protective terminal. The standard thermostat is equipped with terminal cover to prevent accidental contact. Requirement for thermostat without this cover muset be indicated in order. Avoid impacts on stem and head as well as stem deformations during installation. Thermostat well can be ordered as accessory.						
TEMPERATURE SETTING	<ol> <li>Regulation knob - TH 160, TH 160.1, TH 160.2, TH 163, TH 164, TH 166, TH 167 and TH 169. Temperature can be changed in control range by user</li> <li>In manufacturer according to specification in order. Set temperature can not be changed by user (TH 162 and TH 165)</li> </ol>						
Technical data							
	<b>Setting accuracy</b> ±10% from the highest rated switching						
	Secting accuracy     temperature       Stem diameter     8 mm						
					120°C		
	Weight approx. 0,25 to 0,35 kg						
	Protection				IP 00		
	Lifetime				10 000 cycles		
	Туре	Control range [°C]	Switching difference [K]	Stem length L <sub>1</sub> ±3 [mm]	Thermostat length	Rated voltage, rated current	Number of terminals
	TH 160	20-80	2÷8	315	388	250 V, 15 A AC	2
	TH 160.1	20-75	2÷8	315	388	250 V, 15 A AC	2
	TH 160.2	20-80	2÷8	315	388	250 V, 15 A AC	3
	TH 162	20-160	1÷16	100	164	250 V, 15 A AC	3
	TH 163	50-90	6÷16	100	173	250 V, 15 A AC	3
	TH 164	30-160	2÷10	160	233	250 V, 15 A AC	3
	TH 165	20-200	1÷10	160	224	250 V, 15 A AC	3
	TH 166	100-200	1÷10	200	273	250 V, 15 A AC	3
	TH 167	20-100	1÷10	150	323	250 V, 15 A AC	3
	TH 167.1	-10-50	1÷10	150	323	250 V, 15 A AC	3

## **TECHNICAL DRAWINGS**





Contacts

## APATOR METRA s.r.o.

Havlíčkova 919/24 787 O1 Šumperk Czech Republic

 Tel.:
 +420 583 718 261

 E-mail:
 prodej@metra-su.cz

 Web:
 www.metra-su.cz

Your distributor:

The manufacturer reserves the right to change design, technical specifications and accesories without prior notice.

K2O24/O3a